

Spectralink 7202

Durable, Robust, and Feature-rich Handset



The Spectralink 7202 is designed for long-term dependability and increased mobility in specialised working environments. The functionalities of the robust and feature-rich handsets make them a valuable working tool for personnel within industries such as retail and healthcare. Moreover, the flexible menu structure allows the handset to be customised to specific vertical markets.

With these handsets, employees will benefit from being able to move around the company freely while constantly being accessible.

For the employee on-the-move, battery life is of utmost importance. These handsets use temperature compensated charging, which allows for quick recharging without damaging the batteries.

Spectralink 7202 Handset

The Spectralink 7202 is a robust, well-designed, feature-rich and price competitive handset. It meets the demands for mobility and is built for long-term dependability in harsh environments.

BENEFITS

- Customise the handset with third-party applications
- Delivers exceptional voice quality without any background noise, echo, delay, or interruptions
- Resistant to drops and shocks making the handsets more durable
- Allows mobile employees to work more efficiently with extended battery life and quick recharging

FEATURES

SPECTRALINK 7202

- Colour display
- Date and time in display*
- Auto key lock
- 12 different ringtones and adjustable ring volume
- Special ring tones for noisy environments
- Auto login – roaming between two different installations
- Auto-answer (B-answer)
- Alarm key – ready for alarm application**
- Alarm key speed dial
- CLIP
- Telephone book with 50 entries
- Call list of incoming/missed/received calls (up to 40 calls)
- Text message
- LED indication of incoming and unanswered calls
- Full Slot DECT radio
- Software Update Over The Air (SUOTA)
- 14 menu languages (UK, FR, DE, ES, IT, NL, CZ, PL, DK, NO, SV, FI, PT, RU)

* System dependent feature. See Feature Reference Guide on support pages at www.support.spectralink.com for details.

** Application dependent feature

SPECIFICATIONS

APPROVALS

- EMC:
 - EN 301 489-1
 - EN 301 489-6

SIZE AND WEIGHT

- Size: 149 x 50 x 28 mm (5.9 x 2.0 x 1.1 in.)
- Weight: 123 g incl. battery (4.3 oz incl. battery)

SPEECH / STANDBY TIME

- Speech time: up to 23 (27 hours in economy mode)
- Standby time: up to 118 hours

BATTERY

- Battery: Li-ion battery
- Easily removable battery with option to use in shift-operation environments
- Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

TEMPERATURE

- Operating temperature: 0 - 40° C (32° - 104° F)
- Charging temperature: 0 - 25° C (32° - 77° F)

TESTS

- Drop test: IEC 60068-2-32

7202 / CISCO SKUs

- SP-SLNK-7202-EU (EMEA)
- SP-SLNK-7202-AU (Australia)
- SP-SLNK-7202-NZ (New Zealand)
- SP-SLNK-7202-NA (North America / Canada)

Learn More

Learn what Spectralink wireless telephones, in partnership with Cisco®, can do for your organisation. Visit us at spectralinkplus.com or call your Spectralink representative.



spectralinkplus.com
spectralinkplus@spectralink.com
+1 303-441-7576 North America
+44 (0) 7802 537909 EMEA