

Spectralink IP-DECT Base Station

Over the air call signalling between your
DECT server and handsets



The Spectralink IP-DECT Base Station controls the traffic in the air and provides the link between Spectralink wireless handsets and Spectralink DECT Servers. The Spectralink IP-DECT Base Station interoperates with the entire Spectralink DECT Server portfolio.

The Spectralink IP-DECT Base Stations can be powered by Power Over Ethernet (POE) IEEE 802.3af or an external power supply.

Each Spectralink IP-DECT Base Station has 12 speech channels and covers a circular area between 66 and 985 feet (20-300 metres) in diameter. Because coverage depends on location specifics such as building materials and interference, a site assessment before installation helps to determine the proper number and placement of base stations. An External Antenna can be attached to extend or direct coverage where needed.

SPECIFICATIONS

NETWORK AND PROVISIONING

- 10/100 Mbps Ethernet port
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronisation from the Spectralink DECT Server
- Event logging
- LED status indication

RADIO INTERFACE

- RF Output 20 to 24 dBm at antenna connection
- Sensitivity: typical -90 dBm measured at antenna connection at BER =0.001
- Typical range:
 - Indoor: 20-50 m. (65.6 - 164 ft.)
 - Outdoor: 300 m. (984.3 ft.)
- Full slot DECT radio (12 channels)

ELECTRO MAGNETIC COMPATIBILITY APPROVALS (REGULATORY STANDARDS)

- EN 301 489-1
- EN 301 489-6
- FCC RULES, FCC PART15, SubpartD; RSS-213
- IC Rules RSS213 Issue 2

SAFETY (REGULATORY STANDARDS)

- UL60950-1 CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1

DECT APPROVAL

- EN 301 406

ELECTRICAL REQUIREMENTS

- Power over Ethernet (IEEE 802.3af), Class 1 device
- Typical power consumption: 2W per unit
- External power supply option
- External antenna connection
(Only Spectralink external antenna can be used)

ENVIRONMENTAL CONDITIONS

- Operating temperature: -10° - 40° C (50° - 104° F)
- Storage temperature: -50° - 70° C (-58° - 158° F)
- Relative humidity: Between 20% and 80% (non-condensing)
- The equipment is in compliance with the requirements of EU directive 2002/95/EC (ROHS) and 2002/96/EC (WEEE)

PHYSICAL CHARACTERISTICS

- Size: 100 x 38 x 100 mm (3.9 x 1.2 x 3.9 in.)
- Weight: 120 gr. (4.2 oz)
- Grey-white (NCS 0502-Y)
- Wall-mountable, indoor
- Can be mounted upside down

The Spectralink IP-DECT Base Station is regulatory-certified for frequency bands used in North America, Europe, Australia and New Zealand.

Learn More

Learn what Spectralink wireless telephones, in partnership with Cisco®, can do for your organisation. Visit us at spectralinkplus.com or call your Spectralink representative.



spectralinkplus.com
spectralinkplus@spectralink.com
+1 303-441-7576 North America
+44 (0) 7802 537909 EMEA