

PIVOT™

by spectralink

Product Specifications



PIVOT™ (Spectralink 87-Series) handsets deliver enterprise-grade, on-site voice mobility with a user-friendly interface and reliable access to critical business applications.

Based on the Android™ operating system, it is a WorkSmart solution, meaning it has the perfect balance of Smartphone-like usability and the quality and reliability you need for work. It is differentiated by its intuitive touchscreen design, HD voice quality, seamless Voice over Wi-Fi roaming without dropouts, durability, broad telephony and WLAN interoperability, and predictable return on investment.

To achieve superior voice quality in unique enterprise environments, PIVOT is built with Spectralink Voice Quality Optimization, VQO, a patented, engineered system that delivers superior voice quality. The system is built of technology on the inside of each Spectralink device, and the knowledge and expertise of our partners and specialized system architects, on the outside.

PIVOT further enhances the customer value proposition with Google™ Mobile Services certification and two standards-based application interfaces. In partnership with the Spectralink applications development ecosystem, PIVOT enables new opportunities for end-user productivity solutions.



FEATURE OVERVIEW

OVERVIEW

- Spectralink's high performance audio and voice over WLAN implementation known as Spectralink Voice Quality Optimization (VQO)
- Enterprise SIP and WLAN features
- Home page, user interface, settings utility and applications are based on the Android platform.
- Google™ Mobile Services (GMS) including Google Play™ and other standard Google applications
- Highly customizable platform via optional feature licenses
- Large, optically bonded, damage-resistant glass touchscreen
- Multi-touch pan, zoom, swipe-gesture navigation
- Extended battery life, user-replaceable and hot-swappable batteries
- Dedicated hard buttons for emergency dial (red button), scanning and Push-to-Talk (PTT)
- Chemical resistance to commonly used cleaning solutions
- Secure Over-the-Air (OTA) provisioning and management
- 8MP rear-facing camera

GENERAL FEATURES

PROCESSOR AND MEMORY

- ARM Cortex-A9 dual core, 1 GHz processor
- 1 GB DRAM, 16GB Flash

OPERATING SYSTEM

- Android™ 5.1.1 Lollipop
- Protected from jail-breaking and rooting

DISPLAY AND TOUCHSCREEN

- 4.3 in. (109 mm) TFT, 800 x 480 pixels
- 16 million color palette
- Multi-touch capacitive touch screen display
- Accelerometer-based automatic screen orientation
- Manual or automatic adjustable display brightness
- Backlit display with adjustable time out
- Selectable wallpaper/background

PERIPHERAL INTERFACES

- Micro USB interface for wall charging and configuration
- 3.5 mm four-conductor stereo headset connector

BATTERY

- Easy-access, replaceable battery pack – 2200 mAh
- Up to eight hours talk time
- Up to 90 hours standby time
- Hot swap option

Talk and standby time may vary based on scanner, applications usage, screen brightness settings, etc.

PHYSICAL CHARACTERISTICS

DURABILITY

- Drop/shock: MIL STD 810G, method 516.6 procedure IV
- Ingress protection standard: IP-64 per IEC 60529
- Damage-resistant Dragontrail™ glass

ENVIRONMENTAL

- Operational temperature: 32 - 104° F (0 - 40° C)
- Storage temperature: -22 - 140° F (-30 - 60° C)

DIMENSIONS & WEIGHT*

PIVOT:SC 8744	
Dimensions	5.7 x 3 x .75 in. (144.6 x 77.2 x 19 mm)
Weight	8.5 oz (240 gr.)

*As measured with battery installed.

WIRELESS NETWORKING: WI-FI

BAND	FREQUENCY	DATA RATES
802.11a	5.15 - 5.25 GHz	6, 9, 12, 18, 24, 36, 48, 54 Mbps
	5.25 - 5.35 GHz	
	5.47 - 5.725 GHz	
	5.725 - 5.825 GHz	
802.11b	2.4 - 2.4835 GHz	1, 2, 5.5, 11 Mbps
802.11g	2.4 - 2.4835 GHz	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	2.4 and 5 GHz	21.7, 43.3, 65, 72.2 Mbps

2.4GHz and 5GHz dynamic band roaming supported

802.11n single-stream, 20MHz channel with SGI

TELEPHONY FEATURES

USABILITY

- Intuitive, instantly-familiar user interface
- Choice of two patent-pending ergonomic grip and profile options
- Backlit display with automatic brightness control and proximity sensor
- Multilingual user interface (English, French, Spanish, German, Italian)
- Speech-to-text for all supported languages

SPECTRALINK SAFE-PERSONAL SAFETY

- Duress/panic button
- Motion detectors: Man down, running and no movement
- Alarm notifications

SIP CALL HANDLING FEATURES

- Call hold/resume
- Music on hold (server-provided)
- Consultation hold
- Call transfer (attended/unattended)
- Three-way conferencing (local)
- Call screening (incoming/outgoing)
- Call park/retrieve
- Call waiting
- Multiple calls per line
- Message Waiting Indicator (MWI)

- Do not disturb (silence or vibrate modes)
- Calling party ID (name and number)
- Connected party ID (name and number)
- Call forward
- Call reject
- Audible and vibrate notification options
- Speed dial
- Contact directory with support for 1000s of local entries
- Call logs with up to 1000 entries for incoming, outgoing and missed calls

Summary only – actual feature support will vary among call platforms

CODECS

- G.711 (A-law and μ -law), G.729, G.722

PUSH-TO-TALK

- On-board native 'walkie-talkie' capability
- One-to-one, one-to-many broadcast communication
- 24 configurable channels
- Priority, default channel

ADDITIONAL TELEPHONY FEATURES

- Predictive dialing from contacts list
- Recent call lists
- Call Server Failover

MANAGEMENT

CONFIGURATION AND PROVISIONING

- Initial provisioning via USB
- Administrator login and privileges
- Remote Over-the-Air (OTA) configuration management of administrative settings
- Remote Over-the-Air (OTA) system upgrade, under administrative control
- Third-party MDM interoperable, for administrative settings
- Spectralink Configuration Management System (CMS)
 - custom server-based centralized provisioning and configuration tool for high-speed mass deployment
- Spectralink Quick Network Connect (QNC) Tool compatible

PERFORMANCE AND FAULT MANAGEMENT

- On-board diagnostics tools
- Syslog reporting
- Roaming and hand-off reporting
- Event logging
- Status reporting

PERFORMANCE

QUALITY OF SERVICE (QOS)

- Wi-Fi Multimedia (WMM)
- WMM-Power Save
- WMM-Admission Control
- DSCP tagging

SECURITY

- WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-FAST, EAP-TLS, PEAP-MSCHAPv2) with Opportunistic Key Caching (OKC) and Cisco Client Key Management (CCKM)
- HTTPS secure configuration and monitoring
- Signed software executables

APPLICATION TOOLS

APPLICATION DEVELOPMENT

- Standards-based web API
- On-board, enhanced browser (JavaScript, CSS, DOM) for rich application integration
- Access to a broad universe of Android applications
- Google™ Mobile Services (e.g., Google Play™ store, Google™ search, Calendar Sync, Contacts Sync, Android WebView etc.)

EXCHANGE SERVER INTEGRATION

- Calendar
- Contacts
- E-mail

IMAGING

REAR-FACING CAMERA

- 8 MP
- 3296 x 2460 resolution (4:3 aspect ratio)
- *f* 2.4 lens
- Focus range: 10 cm - infinite

NETWORKING

NETWORKING STANDARDS

- Manual or Dynamic Host Configuration Protocol (DHCP)
- Domain Name Service (DNS)
- Simple Network Time Protocol (SNTP)
- Lightweight Directory Access Protocol (LDAP)
- XML and XHTML

SPECIFICATIONS

SPECTRALINK PIVOT:SC 8744 / CISCO SKUs

- SLINK-8744-EMEA (Europe / Middle East / Africa)
- SLINK-8744-NA (North America / Canada)
- SLINK-8744-AUS (Australia / New Zealand)

[Learn More](#)

Learn what Spectralink wireless telephones, in partnership with Cisco®, can do for your organization. Visit us at spectralinkplus.com or call your Spectralink representative.

Android, Google, Google Play and other marks are trademarks of Google, Inc.



spectralinkplus.com
spectralinkplus@spectralink.com
+1 303-441-7576 North America
+44 (0) 7802 537909 EMEA